

DRYING OVEN WITH PLATFORM CART

STANDARDS: EN 932-5, EN 1097-5, ASTM C 127, C136, D558, D559, D560, D698, D1557, D1559, BS 1924:1, BS 1377:1, UNE 103300

Drying Oven with Platform Carts are especially suitable where high temperature uniformity and precision inside the chamber are required.

Drying Ovens are fan circulated.

The accuracy of the temperature and its uniformity are granted within the tolerances requested by the Standards.

The interior is made from stainless steel and the exterior is robustly constructed from sheet steel finished in powder coated paint.

Temperature range is from ambient +10°C to 250°C. Control System is Digital PID Controller.

The Ovens are equipped of a dual safety thermostat with higher thermic threshold to prevent accidental over-temperatures and to ensure safe working conditions.

The Ovens are supplied complete with 8 shelves easily removable and that can be positioned at various heights. Shelves are placed on a wheeled Platform cart. The platform cart has handles for ease of pulling.

Please contact our company for different capacities.



HR-A1550

Technical Specifications:

| Product Code | Product Name | Capacity (lt) | Power Supply |
|--------------|------------------------------------|---------------|-----------------------|
| HR-A1550 | Laboratory Oven with Platform Cart | 4000 | 380 V, 50-60 Hz, 3 ph |

Spare Parts & Accessories:

| Product Code | Product Name |
|--------------|---------------------|
| HR-A1550/1 | Shelve for HR-A1550 |

